



## Product specification

## RollerHook - Assembled

**General**

|              |  |
|--------------|--|
| Cat. Number  | <b>541as</b>   |
| Sub-category | Hooks  |
| Yield Type   | Tomato/Cucumber  |
| Description  | RollerHook assembled. Rollerhook specially designed to ensure a full control of plant's lowering at minimum cost, the Roller Hook is composed of a reusable multi-seasonal metal frame and a strong disposable spool with up to 48 meters of PP UV resistant twine. Bio twine is optional. |
| Spool Color  | Black / White  |
| Twine Color  | Black / White / Color / Bio Twine  |

**Material:**

|            |  |
|------------|--|
| Spool      | Polypropylene + Anti-UV Additive                           |
| Twine      | Polypropylene + Anti-UV Additive<br>or Biodegradable twine |
| Metal part | Galvanized Iron  |

**Technical Specifications**

| Parameter                     | Value                             | Unit  |
|-------------------------------|-----------------------------------|-------|
| Twine length<br>PP twine 1500 | Up to 48                          | meter |
| Twine length<br>PP twine 1200 | Up to 36                          | meter |
| Spool Weight                  | Depends on twine type and length  | Gr    |
| Metal part weight             | 22.7                              | Gr    |
| Suitable for wire<br>diameter | 2.5-4                             | Mm    |
| Carrying force                | Up to 10, depending on twine type | Kg    |

**Durability**

|        |  |
|--------|--|
| Spool  | Up to 3 years for PP twine only  |
| Twine* | 1. The exposed twine is good for 1 season (up to 1 year) on the condition the twine is released and the plant is lowered at least 4 times during the season.<br>2. The non-released twine is ready for the next season under the terms mentioned in paragraph 1. |

## greenhouse solutions

Note: The exposure to light of the non-released twine starts from the last releasing of the former season.

\*Not including bio twine

Metal Part

Multi-seasonal

**Storage**

In a cool, dry place

- away from heat
- away from direct sunlight
- storage temperature should not exceed 60°C

**Packaging**

Units per box: 350 pcs

Box weight: approx. 10-25 Kg. Depends on twine length and type.

Boxes per pallet: 32/28

Box Size (L x W x H cm): 56 x 48 x 27

**Installation temp.  
range (°C)**

N/A